

Canada
 Cam-Concept Inc
 145, rue de la défense nationale
 St-Raymond, QC, G3L 4Y4
info@hooklifttrailer.com
 418-987-8282



USA
 Cam-Concept USA, LLP
 2255 Glendale Ave Suite 3
 Sparks, Nevada, 89943 1
info@hooklifttrailer.com
 775-232-2489

CAM-PACK SYSTEM SPECIFICATIONS

Size	10 cubic yards, 12 ft body	20 cubic yards, 16 ft body
Overall length	191"	240"
Width	86"	96"
Height above hook lift	72"	86"
Overall height (trailer / truck mounted version)	84" / 110"	98" / 124"
Recommended hook lift minimum capacity	10 000 lbs	18 000 lbs
Minimum trailer GTWR	14 000 lbs	24 000 lbs
Minimum truck GVWR	19 500 lbs	31 000 lbs
Approx. body weight	5 000 lbs	8 000 lbs
Compaction rate (recycling / garbage)	375 / 600 lbs/cuyd	325 / 500 lbs/cuyd
Carrier cylinders (2x)	3,5" bore, 1,75" rod	4" bore, 2" rod
Packer Cylinders (2x)	2,5" bore, 1,5" rod	3" bore, 1,5" rod
Tailgate cylinders (2x)	2,5" bore, 1,5" rod	3" bore, 1,5" rod
Body sub-frame	C6@8,2 channel	
Body walls	10 GA, 50W steel	
Body roof	10 GA, 50W steel	
Body floor	10 GA, 50W steel	
Tailgate walls	10 GA, 50W steel	
Hopper floor plate	3/16" , CHT100 steel	
Electric system	All LED light, connect to your hook lift with a standard trailer 7 pin connector	
Hydraulic system	Connect to your hook lift hydraulic system with 2X -08 Parker quick connections	

AVAILABLE OPTION	
Single cart tipper with hydraulic controll	

Unique design without ejector. The body has a tapered shape to ease the ejection. It uses your hook lift dumping cylinders to eject the material.

